

5

## CLAIMS

We claim:

- 530 A17
1. A method to train image classification, comprising  
measuring noise in a first image; and  
training a classification model from the noise to classify a second image as a  
natural image versus an artificial image from noise.
  2. The method of claim 1, wherein measuring noise further comprises:  
generating a noise-reduced third image from the first image;  
determining the difference between the first image and the third image;  
and  
aggregating the difference into a noise feature vector, and  
wherein training a classification model from the noise further comprises:  
training a classification model from the noise feature vector.
  3. The method of claim 1, wherein generating a noise-reduced third image further  
comprises:  
applying a median filter to the first image.
  4. The method of claim 1, wherein generating a noise-reduced third image further  
comprises:  
applying a Gaussian filter to the first image.
  5. The method of claim 1, wherein generating a noise-reduced third image further  
comprises:  
applying a Wiener filter to the first image.
  6. The method of claim 1, wherein the first image further comprises a frame in a  
video stream.

- 5 7. A method to train image classification, comprising:  
generating a feature vector from an image; and  
training a classification model to classify a second image as a slide image versus a  
comic image, from the feature vector.
- 10 8. The method of claim 7, wherein generating a feature vector from an image further  
comprises:  
generating an aggregated feature vector from an image.
- 15 9. The method of claim 7, wherein generating a feature vector from an image further  
comprises:  
generating a feature vector from any combination of at least one feature of an  
image selected from the group consisting of at least one text block feature  
of the image, at least one edge feature of the image, at least one aspect  
ratio of the image.
- 20 10. The method of claim 7, wherein the image further comprises a frame in a video  
stream.
- 25 11. A method to classify an image as a slide image versus a comic image, comprising:  
receiving a feature vector of the image;  
classifying the image as slide image versus comic image, from the feature vector;  
and  
generating the classification of the image.
- 30 12. The method of claim 11, wherein the classification is performed on a set of video  
frames of a video sequence, and the most likely classification result emerging out of the  
classification results of the individual frames is taken as the class of the video sequence.
- 35 13. The method of claim 11, further comprising:

5 generating a feature vector from any combination of at least one feature of an image selected from the group consisting of at least one text block feature of the image, at least one edge feature of the image, at least one aspect ratio of the image;

10 14. A method to classify an image as natural image versus artificial image, further comprising:

receiving a feature vector of the image;

classifying the image as natural image versus artificial image, from the feature vector; and

15 generating the classification of the image.

15. The method of claim 14, wherein the classification is performed on a set of video frames of a video sequence, and the most likely classification result emerging out of the classification results of the individual frames is taken as the class of the video sequence.

20 16. The method of claim 14, wherein the feature vector further comprises a noise vector.

17. The method of claim 14, wherein the feature vector further comprises a sharpness vector.

25 18. An image classification system comprising:  
a feature extraction component, extracting a feature that distinguishes an image between a naturally-looking image versus an artificially-looking image;  
30 and  
a training system, operably coupled to the feature extraction component.

19. The system of claim 18, wherein the image further comprises a frame in a video stream.

5 20. The system of claim 18, wherein the classification is performed on a set of video frames of a video sequence, and the most likely classification result emerging out of the classification results of the individual frames is taken as the class of the video sequence.

10 21. A system to classify an image comprising:  
a processor;  
a storage device coupled to the processor;  
software means operative on the processor to train classification of at least one of images as either a natural image or an artificial image.

15 22. The system of claim 21, wherein the at least one image further comprises at least one frame in a video stream.

20 23. The system of claim 21, wherein the software means further comprises:  
a generator of a noise vector of each of the at least one image.

25 24. A system to classify an image, comprising:  
a processor;  
a storage device coupled to the processor;  
software means operative on the processor to train classification of at least one image as either a slide image or an comic image.

25. The system of claim 24, wherein the at least one image further comprises at least one frame in a video stream.

30 26. The system of claim 24, the software means further comprising:  
a generator of a feature vector from any combination of at least one feature of an image selected from the group consisting of at least on text block feature of the image, at least one edge feature of the image, at least one aspect ratio of the image.

57 27. A system to classify an image, comprising:  
a processor;  
a storage device coupled to the processor; and  
software means operative on the processor to classify an image as either a natural  
image or an artificial image.

10 28. The system of claim 27, wherein the image further comprises a frame in a video  
stream.

15 29. The system of claim 27, wherein the software means further comprises:  
a generator of a noise vector of the image.

20 30. A system to classify an image, comprising:  
a processor;  
a storage device coupled to the processor; and  
software means operative on the processor to classify an image as either a slide  
image or an comic image.

25 31. The system of claim 30, wherein the image further comprises a frame in a video  
stream.

30 32. The system of claim 30, the software means further comprising:  
a generator of a feature vector from any combination of at least one feature of an  
image selected from the group consisting of at least on text block feature  
of the image, at least one edge feature of the image, at least one aspect  
ratio of the image.

33. A computer-readable medium having computer-executable instructions to cause a  
computer to perform a method comprising:  
generating a feature vector from a first image; and

5 training a classification model to classify a second image as a natural image  
versus an artificial image, from the feature vector.

34. The computer-readable medium of claim 33, wherein the first image further  
comprises a frame in a video stream.

10

35. The computer-readable medium of claim 33, wherein the feature vector further  
comprises a noise feature.

36. The computer-readable medium of claim 33, wherein the feature vector further  
15 comprises a edge-sharpness feature.

37. A computer-readable medium having computer-executable instructions to cause a  
computer to perform a method comprising:  
generating a feature vector from a first image; and  
20 training a classification model to classify a second image as a slide image versus a  
comic image, from the feature vector.

38. The computer-readable medium of claim 37, wherein the first image further  
comprises a frame in a video stream.

25

39. The computer-readable medium of claim 37, wherein the generating a feature  
vector from a first image further comprises:  
generating a feature vector from any combination of at least one feature of an  
image selected from the group consisting of at least one text block feature  
30 of the image, at least one edge feature of the image, at least one aspect  
ratio of the image.

40. A computer-readable medium having computer-executable instructions to cause a  
computer to perform a method comprising:  
35 receiving a feature vector of the image;

5 classifying the image as slide image versus comic image, from the feature vector;  
and  
generating the classification of the image.

41. The computer-readable medium of claim 40, wherein the classification is  
10 performed on a set of video frames of a video sequence, and the most likely classification  
result emerging out of the classification results of the individual frames is taken as the  
class of the video sequence.

42. The computer-readable medium of claim 39, wherein the method further  
15 comprises:

generating a feature vector from any combination of at least one feature of an  
image selected from the group consisting of at least one text block feature  
of the image, at least one edge feature of the image, at least one aspect  
ratio of the image.

20 43. A computer-readable medium having computer-executable instructions to cause a  
computer to perform a method comprising:  
receiving a feature vector of the image;  
classifying the image as natural image versus an artificial image, from the feature  
25 vector; and  
generating the classification of the image.

44. The computer-readable medium of claim 42, wherein the classification is  
performed on a set of video frames of a video sequence, and the most likely classification  
30 result emerging out of the classification results of the individual frames is taken as the  
class of the video sequence.

45. An apparatus to classify at least one image, comprising:  
a processor;  
35 a storage device coupled to the processor; and

5 a software component operative on the processor to train classification of at least one image as either a natural image or an artificial image.

46. The apparatus of claim 44, wherein the at least one image further comprises at least one frame in a video stream.

10

47. The apparatus of claim 44, wherein the software component further comprises: a generator of a noise vector of each of the at least one image.

48. An apparatus to classify at least one image, comprising:  
a processor;  
a storage device coupled to the processor;  
a software component operative on the processor to train classification of at least one image as either a slide image or an comic image.

20 49. The apparatus of claim 47, wherein the at least one image further comprises at least one frame in a video stream.

50. The apparatus of claim 47, the software component further comprising:  
a generator of a feature vector from any combination of at least one feature of an image selected from the group consisting of at least on text block feature of the image, at least one edge feature of the image, at least one aspect ratio of the image.

25

51. An apparatus to classify an image, comprising:  
a processor;  
a storage device coupled to the processor; and  
a software component operative on the processor to classify an image as either a natural image or an artificial image.

30



5 52. The apparatus of claim 51, wherein the classifying is performed on a set of video frames of a video sequence, and the most likely classification result emerging out the classification results of the individual frames is taken as the class of the video sequence.

10 53. The apparatus of claim 51, wherein the software component further comprises:  
a generator of a noise vector of the image.

54. The apparatus of claim 51, wherein the software component further comprises:  
a generator of a sharpness vector of the image.

15 55. An apparatus to classify an image, comprising:  
a processor;  
a storage device coupled to the processor; and  
a software component operative on the processor to classify an image as either a  
slide image or an comic image.

20 56. The apparatus of claim 55, wherein the classifying is performed on a set of video frames of a video sequence, and the most likely classification result emerging out the classification results of the individual frames is taken as the class of the video sequence.

25 57. The apparatus of claim 55, the software component further comprising:  
a generator of a feature vector from any combination of at least one feature of an  
image selected from the group consisting of at least on text block feature  
of the image, at least one edge feature of the image, at least one aspect  
ratio of the image.

30 58. A method to train image classification, comprising:  
measuring sharpness in a first image; and  
training a classification model from the sharpness, to classify a second image as a  
natural image versus an artificial image, from sharpness.

- 5 59. The method of claim 58, wherein measuring sharpness further comprises:  
generating a blurred third image from the first image;  
determining the difference between the first image and the third image; and  
aggregating the difference into a sharpness feature vector, and  
wherein training a classification model from the sharpness feature vector further  
10 comprises:  
training a classification model from the sharpness feature vector.
60. The method of claim 58, wherein generating a blurred third image from a first  
image further comprises:  
15 applying a Gaussian filter to the first image.
61. The method of claim 58, wherein the first image further comprises a frame in a  
video stream.
- 20 62. The method of claim 58, wherein the first image further comprises all frames in a  
video stream.